

# XZA®

The all-position radial with proven versatility.



- Massive shoulders and application specific compound help resist scrub and abrasion, extending tread life.
- Zigzag groove design for true all-position use.
- Application specific compounding helps improve resistance to scrub and abrasion.

## Specifications for Tread Design: XZA®

Size	Load Range	Catalog Number	Tread Depth 32nds	Max Speed mph	Loaded Radius		Overall Diameter		Overall Width		Approved Rims	Min. Dual Spacing		Revs per Mile	Max. Tire Load Single				Max. Tire Load Dual			
					in.	mm.	in.	mm.	in.	mm.		in.	m		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
10R17.5	G	05008	16	65	15.6	397	33.9	861	9.5	241	6.75, 7.50	11.1	282	615	4805	115	2180	790	4540	115	2060	790
8R19.5	F	60893	16	75	15.6	395	33.6	854	8.1	206	5.25, 6.00	8.8	224	616	3525	110	1600	760	3305	110	1500	760
305/70R19.5	J	50505	18	75	16.7	424	36.3	922	11.8	300	8.25, 9.00	13.1	334	575	6940	120	3150	830	6395	120	2900	830
365/70R22.5	L	71842	19	75	19.6	497	42.5	1080	14.3	363	10.5			490	10500	125	4750	860				

Note: Rim listed first is the measuring rim.  
Exceeding the lawful speed limit is neither recommended nor endorsed.  
Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.  
Michelin® tires and tubes are subject to a continuous development program. Michelin North America, Inc. reserves the right to change product specifications at any time without notice or obligations.  
Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

**WARNING! SERIOUS INJURY MAY RESULT FROM:**  
\*TIRE FAILURE DUE TO UNDERINFLATION/OVERLOADING OR MISAPPLICATION -- FOLLOW TIRE PLACARD INSTRUCTIONS IN VEHICLE. CHECK INFLATION PRESSURE FREQUENTLY WITH AN ACCURATE GAUGE  
\*EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING -- ONLY SPECIALLY TRAINED PERSONS SHOULD MOUNT TIRES. WHEN MOUNTING, USE SAFETY CAGE AND CLIP-ON EXTENSION AIR HOSE TO INFLATE.  
CONSULT OWNER'S MANUAL FOR ADDITIONAL SAFETY INFORMATION

## Load and Inflation Tables: XZA®

S = Single configuration, or 2 tires per axle.  
D = Dual configuration, or 4 tires per axle.

### 10R17.5 LRG

PSI	85	90	95	100	105	110	115	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa	590	620	660	690	720	760	790						
LBS	SINGLE	7720	8010	8300	8600	8940	9280	9610	S	4805	LBS at	115	PSI
	DUAL	14560	15140	15720	16320	16940	17560	18160	D	4540	LBS at	115	PSI
KG	SINGLE	3500	3640	3780	3900	4060	4220	4360	S	2180	KG at	790	kPa
	DUAL	6600	6880	7160	7400	7680	7960	8240	D	2060	KG at	790	kPa

If you require information on this tire for RV purposes please go to [www.michelinrvtires.com](http://www.michelinrvtires.com)

### 8R19.5 LRF

PSI	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa	480	520	550	590	620	660	690	720	760						
LBS	SINGLE	5080	5360	5670	5910	6150	6390	6610	6830	7050	S	3525	LBS at	110	PSI
	DUAL	9840	10280	10720	11140	11560	12000	12400	12800	13220	D	3305	LBS at	110	PSI
KG	SINGLE	2300	2440	2570	2680	2800	2900	3000	3100	3200	S	1600	KG at	760	kPa
	DUAL	4480	4680	4860	5040	5240	5440	5640	5840	6000	D	1500	KG at	760	kPa

If you require information on this tire for RV purposes please go to [www.michelinrvtires.com](http://www.michelinrvtires.com)

### 305/70R19.5 LRJ

PSI	75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL		
kPa	520	550	590	620	660	690	720	760	790	830		S	6940	LBS at 120 PSI
LBS	SINGLE	9530	10030	10530	11030	11510	12000	12470	12950	13420	13880	D	6395	LBS at 120 PSI
	DUAL	17560	18500	19420	20320	21220	22100	22980	23860	24720	25580	S	3150	KG at 830 kPa
KG	SINGLE	4340	4540	4800	4980	5240	5440	5620	5880	6060	6300	D	2900	KG at 830 kPa
	DUAL	7960	8360	8840	9200	9640	10000	10360	10800	11160	11600			

### 365/70R22.5 LRL

PSI	80	85	90	95	100	105	110	115	120	125		MAXIMUM LOAD AND PRESSURE ON SIDEWALL		
kPa	550	590	620	660	690	720	760	790	830	860		S	10500	LBS at 125 PSI
LBS	SINGLE	14700	15420	16140	16860	17560	18260	18960	19640	20400	21000	D		LBS at PSI
	DUAL											S	4750	KG at 860 kPa
KG	SINGLE	6640	7020	7320	7680	7960	8240	8600	8880	9240	9500	D		KG at kPa
	DUAL													

**If you require information on this tire for RV purposes please go to [www.michelinrvtires.com](http://www.michelinrvtires.com)**

Industry load and inflation standards are in a constant state of change, and Michelin continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

**NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.**